

Pyroil™ CARB & THROTTLE BODY CLEANER

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000515 Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : PYROIL CARB & TBC AERO 12/13OZ

Product code : PYC16

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : 720 Vaiden Drive, Hernando, MS 38632

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone num: 1-80

ber

: 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : CLEANER

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable aerosols : Category 1

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Acute toxicity (Dermal) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity

- single exposure

Category 1 (Central nervous system, Eyes)

Specific target organ toxicity

- single exposure

: Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity

- repeated exposure

Category 2 (Auditory system)

Aspiration hazard : Category 1



Pyroil™ CARB & THROTTLE BODY CLEANER

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000515 Date of first issue: 05/23/2016

GHS label elements

Hazard pictograms







Signal word : Danger

Hazard statements : Extremely flammable aerosol.

Harmful if swallowed, in contact with skin or if inhaled.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

Causes damage to organs (Central nervous system, Eyes). May cause damage to organs (Auditory system) through pro-

longed or repeated exposure.

Precautionary statements

Prevention:

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor. IF ON SKIN: Wash with plenty of water. Call a POISON

CENTER/ doctor if you feel unwell.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed: Call a POISON CENTER or doctor/ physician.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding $50 \, ^{\circ}\text{C} / 122 \, ^{\circ}\text{F}$.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.



Pyroil™ CARB & THROTTLE BODY CLEANER

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000515 Date of first issue: 05/23/2016

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Acetone	67-64-1	>= 50 - < 70
Methanol	67-56-1	>= 20 - < 30
Xylene	1330-20-7	>= 20 - < 30
Ethylbenzene	100-41-4	>= 5 - < 10
Carbon dioxide	124-38-9	>= 5 - < 10

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

IF INHALED: Call a POISON CENTER/ doctor if you feel un-

well.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If on clothes, remove clothes.

Call a physician or poison control centre immediately.

Remove contaminated clothing. If irritation develops, get med-

ical attention.

If on skin, rinse well with water.

Wash contaminated clothing before re-use. If skin irritation persists, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Obtain medical attention.

Do NOT induce vomiting. Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms : Harmful if swallowed, in contact with skin or if inhaled.



Pyroil™ CARB & THROTTLE BODY CLEANER

Version **Revision Date:** SDS Number: Date of last issue: 04/10/2024 04/23/2025 60000000515 Date of first issue: 05/23/2016 3.4

and effects, both acute and

delayed

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

Causes damage to organs.

May cause damage to organs through prolonged or repeated

exposure.

Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.

This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.

This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media Water spray

Carbon dioxide (CO2)

Dry chemical

Alcohol-resistant foam

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

Carbon oxides

Specific extinguishing meth-

ods

Product is compatible with standard fire-fighting agents.

Further information Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.



Pyroil™ CARB & THROTTLE BODY CLEANER

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000515 Date of first issue: 05/23/2016

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Remove all sources of ignition. Ensure adequate ventilation.

Avoid breathing dust.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Evacuate personnel to safe areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Keep away from open flames, hot surfaces and sources of

ignition.

Use only explosion-proof equipment.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Take precautionary measures against static discharges.

Avoid contact with skin and eyes.

Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force

or throw into fire even after use. Do not spray on flames or

red-hot objects.

Keep container tightly closed in a dry and well-ventilated

piace.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

No smoking.

Further information on stor-

age stability

No decomposition if stored and applied as directed.



Pyroil™ CARB & THROTTLE BODY CLEANER

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000515 Date of first issue: 05/23/2016

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.			Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
Acetone	67-64-1	TWA 250 ppm		ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm	NIOSH REL
			590 mg/m3	
		TWA	1,000 ppm	OSHA Z-1
			2,400 mg/m3	
		TWA	750 ppm	OSHA P0
			1,800 mg/m3	
		STEL	1,000 ppm	OSHA P0
			2,400 mg/m3	
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm	NIOSH REL
			260 mg/m3	
		ST	250 ppm	NIOSH REL
			325 mg/m3	
		TWA	200 ppm	OSHA Z-1
			260 mg/m3	
		STEL	250 ppm	OSHA P0
		0.22	325 mg/m3	00111110
		TWA	200 ppm	OSHA P0
		' ' ' ' '	260 mg/m3	0011/110
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
Eury is on Zono	100 11 1	TWA	100 ppm	NIOSH REL
		' ' ' ' '	435 mg/m3	MOONINEE
		ST 125 ppm		NIOSH REL
		545 mg/m3		MOONINEE
		TWA 100 ppm		OSHA Z-1
		435 mg/m3		OOTIAL
		TWA 100 ppm		OSHA P0
		1 ***	435 mg/m3	OUNTO
		STEL		OSHA P0
		STEL 125 ppm 545 mg/m3		OUNTO
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
Carbon Gloxide	124-30-3	STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm	NIOSH REL
		IVVA	9,000 ppm 9,000 mg/m3	NIOSH KEL
		ST 30,000 ppm		NIOSH REL
			54,000 mg/m3	
		TWA	5,000 ppm	OSHA Z-1
			9,000 mg/m3	
		TWA	10,000 ppm	OSHA P0
			18,000 mg/m3	
		STEL	30,000 ppm	OSHA P0
		-·	54,000 mg/m3	

Hazardous components without workplace control parameters

Commonanto	CACNA
Components	l CAS-No.



Pyroil™ CARB & THROTTLE BODY CLEANER

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000515 Date of first issue: 05/23/2016

Xylene 1330-20-7

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sam-	Permissible	Basis
		parameters	specimen	pling time	concentra- tion	
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly- oxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an ap-

proved filter.

In the case of dust or aerosol formation use respirator with an

approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment suppli-

er). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard

gloves that show tears, pinholes, or signs of wear.

Eye protection : Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Wear as appropriate: Impervious clothing Flame-resistant clothing

Safety shoes



Pyroil™ CARB & THROTTLE BODY CLEANER

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000515 Date of first issue: 05/23/2016

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not smoke. When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol

Colour : No data available

Odour : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 56 °C

(1,013 hPa)

The value is calculated

Flash point : -20 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

: 36 %(V)

The value is calculated

Lower explosion limit / Lower

flammability limit

1 %(V)

The value is calculated

Vapour pressure : 307.9 hPa (25 °C)

The value is calculated

Density : 0.8132 g/cm3 (15.56 °C)

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

Heat of combustion : estimated 30.0 kJ/g

Molecular weight : No data available



Pyroil™ CARB & THROTTLE BODY CLEANER

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000515 Date of first issue: 05/23/2016

VOC % By Weight : 42.6 %

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids

Bases
Aluminium
Amines
Ammonia
halogens
Lead
Peroxides
Reducing agents

Strong bases
Strong oxidizing agents

Zinc

Hazardous decomposition

products

Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Eye contact Skin contact Ingestion

Acute toxicity

Harmful if swallowed, in contact with skin or if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 433.88 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 1.62 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 1,171 mg/kg

Method: Calculation method

Components:

Acetone:



Pyroil™ CARB & THROTTLE BODY CLEANER

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000515 Date of first issue: 05/23/2016

Acute oral toxicity : LD50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 76 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 7,426 mg/kg

Methanol:

Acute oral toxicity : LDLo (Humans): 300 mg/kg

Assessment: The component/mixture is toxic after single in-

gestion.

Acute inhalation toxicity : Test atmosphere: dust/mist

Assessment: The component/mixture is toxic after short term

inhalation.

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg

Assessment: The component/mixture is toxic after single con-

tact with skin.

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 - 8,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 6700 ppm

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): ca. 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4000 ppm

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 17,800 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

Acetone:

Result: Possibly irritating to skin



Pyroil™ CARB & THROTTLE BODY CLEANER

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000515 Date of first issue: 05/23/2016

Result: Repeated exposure may cause skin dryness or cracking.

Methanol:

Species: Rabbit

Result: No skin irritation

Xylene:

Assessment: Irritating to skin. Result: Irritating to skin.

Ethylbenzene:

Result: Irritating to skin.

Carbon dioxide:

Assessment: No skin irritation Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Acetone:

Result: Irritating to eyes. Assessment: Irritating to eyes.

Methanol:

Species: Rabbit

Result: Possibly irritating to eyes

Xylene:

Result: Irritating to eyes.

Ethylbenzene:

Result: Irritating to eyes.

Carbon dioxide:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.



Pyroil™ CARB & THROTTLE BODY CLEANER

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000515 Date of first issue: 05/23/2016

Components:

Methanol:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

Ethylbenzene:

Carcinogenicity - Assess-

ment

: Not classifiable as a human carcinogen.

IARC Group 2B: Possibly carcinogenic to humans

Ethylbenzene 100-41-4

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

Causes damage to organs (Central nervous system, Eyes).

Components:

Acetone:

Exposure routes: Inhalation Target Organs: Nervous system

Assessment: May cause drowsiness or dizziness.

Methanol:

Target Organs: Central nervous system, Eyes

Assessment: The substance or mixture is classified as specific target organ toxicant, single ex-

posure, category 1.

Xylene:

Assessment: May cause drowsiness or dizziness., May cause respiratory irritation.



Pyroil™ CARB & THROTTLE BODY CLEANER

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000515 Date of first issue: 05/23/2016

STOT - repeated exposure

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Components:

Ethylbenzene:

Target Organs: Auditory system

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Acetone:

May be harmful if swallowed and enters airways.

Xylene:

May be fatal if swallowed and enters airways.

Ethylbenzene:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.



Pyroil™ CARB & THROTTLE BODY CLEANER

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000515 Date of first issue: 05/23/2016

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

Not permitted for transport

IMDG-Code

UN number : UN 1950
Proper shipping name : Aerosols
Class : 2.1
Subsidiary risk : 6.1

Packing group : Not assigned by regulation

Labels : 2.1 (6.1)
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1950 Proper shipping name : Aerosols

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 ERG Code : 126 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Xylene	1330-20-7	100	496
Xylene	1330-20-7	100	100 (F003)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation



Pyroil™ CARB & THROTTLE BODY CLEANER

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000515 Date of first issue: 05/23/2016

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Methanol 67-56-1 >= 20 - < 30 %

Ethylbenzene 100-41-4 >= 5 - < 10 %


California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, Benzene, which is/are known to the State of California to cause cancer, and Methanol, Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard

Revision Date : 04/23/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN